



ENDUTEX - REVESTIMENTOS TEXTTEIS, SA

VIZELA / PORTUGAL



TECHNICAL DATA SHEET

REFERENCE: BACK X7 FR

DESCRIPTION : PVC DOUBLE COATED HIGH TENACITY POLYESTER FABRIC

COMPOSITION : 68 % PVC
32 % POLYESTER

WIDTH : 160 - 320 - 500 cm

CHARACTERISTIC	SPECIFICATION	METHOD
THICKNESS (mm)	0.42	
TOTAL MASS (g/m ²)	480 ± 40	EN ISO 2286-2
FABRIC MASS (g/m ²)	155 ± 10	EN ISO 2286-2
BREAKING LOAD (daN/50mm)	L.: 250 T.: 200	EN ISO 1421
BREAKING EXTENSION (%)	L.: 20 T.: 25	EN ISO 1421
YOUNG'S MODULUS (N/mm ²)	L.: 600 T.: 400	EN ISO 1421
TEAR STRENGTH (daN)	L.: 20.0 T.: 20.0	DIN 53363
COATING ADHESION (daN/50mm)	min 5.0	EN ISO 2411
COLOUR FASTNESS TO LIGHT	min 5	EN ISO 105-B02
AVERAGE LIGHT TRANSMISSION	20	SF 600 Plus Spectrophotometer
BURNING BEHAVIOUR	B1	DIN 4102

L – Along T - Across

NOTE: Unless otherwise stated, the figures presented shall be regarded as typical values for the material, and not as a minimum to be satisfied.

Date	Revision	QUALITY CONTROL	TECHNICAL MANAGER
2010.03.16	1		