



ENDUTEX - REVESTIMENTOS TEXTEIS, SA

VIZELA / PORTUGAL



---

---

TECHNICAL DATA SHEET

---

---

**REFERENCE: PRINT BWX 500**

**DESCRIPTION** : PVC DOUBLE COATED HIGH TENACITY POLYESTER FABRIC, WITH BLACK SIDE BACK

**COMPOSITION** : 75 % PVC  
25 % POLYESTER

**WIDTH** : 160 – 250 - 320 - 500 cm

CHARACTERISTIC	SPECIFICATION	METHOD
THICKNESS (mm)	0.45	
TOTAL MASS (g/m <sup>2</sup> )	520 ± 40	EN ISO 2286-2
FABRIC MASS (g/m <sup>2</sup> )	130 ± 10	EN ISO 2286-2
BREAKING LOAD (daN/50mm)	L.: 250 T.: 170	EN ISO 1421
BREAKING EXTENSION (%)	L.: 18 T.: 20	EN ISO 1421
TEAR STRENGTH (daN)	L.: 22.0 T.: 18.0	DIN 53363
COATING ADHESION (daN/50mm)	min 5.0	EN ISO 2411
FLAMMABILITY (mm/min)	< 100	DIN 75200

L - Along

T - Across

**NOTE:** This technical data sheet is not legal binding and is based on average results from current production. Unless otherwise stated, values cannot be considered as minimum to be satisfied.

Purchaser is fully responsible for determining the product suitability for its intended application.

Technical details are subject to change without prior notice, so please contact our technical service for any additional information you may require.

Date	Revision	QUALITY CONTROL	TECHNICAL MANAGER
2010.07.01	1		