



ENDUTEX - REVESTIMENTOS TEXTTEIS, SA

VIZELA / PORTUGAL



---

---

TECHNICAL DATA SHEET

---

---

**REFERENCE:** PRINT HX FR

**DESCRIPTION :** PVC DOUBLE COATED HIGH TENACITY POLYESTER FABRIC

**COMPOSITION :** 74 % PVC  
26 % POLYESTER

**WIDTH :** 160 – 320 - 500 cm

CHARACTERISTIC	SPECIFICATION	METHOD
THICKNESS (mm)	0.45	
TOTAL MASS (g/m <sup>2</sup> )	500 ± 40	EN ISO 2286-2
FABRIC MASS (g/m <sup>2</sup> )	130 ± 10	EN ISO 2286-2
BREAKING LOAD (daN/50mm)	L.: 250 T.: 140	EN ISO 1421
BREAKING EXTENSION (%)	L.: 20 T.: 22	EN ISO 1421
TEAR STRENGTH (daN)	L.: 22.0 T.: 16.0	DIN 53363
COATING ADHESION (daN/50mm)	min 5.0	EN ISO 2411
FLAMMABILITY (mm/min)	< 100	DIN 75200
BURNING BEHAVIOUR	B1	DIN 4102

L - Along  
T - Across

**NOTE :** Unless otherwise stated, the figures presented shall be regarded as typical values for the material, and not as a minimum to be satisfied.

Date	Revision	QUALITY CONTROL	TECHNICAL MANAGER
2010.02.09	0		