



ENDUTEX - REVESTIMENTOS TEXTEIS, SA

VIZELA / PORTUGAL



TECHNICAL DATA SHEET

REFERENCE: PRINT LX

DESCRIPTION : PVC DOUBLE COATED HIGH TENACITY POLYESTER WOVEN FABRIC

COMPOSITION : 75 % PVC
25 % POLYESTER

WIDTH : 107 – 160 - 320 cm

CHARACTERISTIC	SPECIFICATION	METHOD
THICKNESS (mm)	0.33	
TOTAL MASS (g/m ²)	450 ± 40	EN ISO 2286-2
FABRIC MASS (g/m ²)	115 ± 10	EN ISO 2286-2
BREAKING LOAD (daN/50mm)	L.: 170 T.: 140	EN ISO 1421
TEAR STRENGTH (daN)	L.: 16.0 T.: 15.0	DIN 53363
COATING ADHESION (daN/50mm)	min 5.0	EN ISO 2411
FLAMMABILITY (mm/min)	< 100	DIN 75200

L - Along
T - Across

NOTE : Unless otherwise stated, the figures presented shall be regarded as typical values for the material, and not as a minimum to be satisfied.

Date	Revision	QUALITY CONTROL	TECHNICAL MANAGER
2010.03.25	1		