



ENDUTEX - REVESTIMENTOS TEXTEIS, SA

VIZELA / PORTUGAL



TECHNICAL DATA SHEET

REFERENCE: PRINT LT 40 FR

DESCRIPTION : PVC DOUBLE COATED HIGH TENACITY POLYESTER SCRIM WITH RELEASE LINER

COMPOSITION : 71 % PVC
29 % POLYESTER

WIDTH : 110 - 137 - 160 cm

CHARACTERISTIC	SPECIFICATION	METHOD
THICKNESS (mm)	0.53	
TOTAL MASS (g/m ²)	330 ± 30 (without Liner)	EN ISO 2286-2
FABRIC MASS (g/m ²)	92 ± 10	EN ISO 2286-2
LINER MASS (g/m ²)	120 ± 12	EN ISO 2286-2
BREAKING LOAD (daN/50mm)	L.: 130 T.: 150	EN ISO 1421
BREAKING EXTENSION (%)	L.: 15 T.: 23	EN ISO 1421
TEAR STRENGTH (daN)	L.: 13.0 T.: 13.0	DIN 53363
COLOUR FASTNESS TO LIGHT	min 6	EN ISO 105-B02
AVERAGE PERMEABILITY OF FABRIC TO AIR (l/m ² /s)	3300	EN ISO 9237
AVERAGE LIGHT TRANSMISSION	32.5	SF 600 Plus Spectrophotometer
BURNING BEHAVIOUR	M2	NF P92-503
BURNING BEHAVIOUR	B1	DIN 4102
OPEN AREA (%)	20	Internal

L - Along T - Across

NOTE 1 : Unless otherwise stated, the figures presented shall be regarded as typical values for the material, and not as a minimum to be satisfied.

NOTE 2 : The results do not include the release liner on the back side, as this one is removed after printing.

Date	Revision	QUALITY CONTROL	TECHNICAL MANAGER
2010.03.10	1		