



ENDUTEX - REVESTIMENTOS TEXTTEIS, SA

VIZELA / PORTUGAL



TECHNICAL DATA SHEET

REFERENCE: POLYCANVAS FR

DESCRIPTION : PVC COATED POLYESTER WOVEN FABRIC

COMPOSITION : 44 % PVC
56 % POLYESTER

WIDTH : 110 – 137 – 160 – 220 – 250 – 320 - 500 cm

CHARACTERISTIC	SPECIFICATION	METHOD
THICKNESS (mm)	0.30	
TOTAL MASS (g/m ²)	260 ± 25	EN ISO 2286-2
FABRIC MASS (g/m ²)	145 ± 10	EN ISO 2286-2
BREAKING LOAD (daN/50mm)	L.: 165 T.: 100	EN ISO 1421
BREAKING EXTENSION (%)	L.: 30 T.: 33	EN ISO 1421
TEAR STRENGTH (daN)	L.: 10.0 T.: 5.0	DIN 53363
FUSION OF PVC COATING	Complete	BS 3424.25A
FLAMMABILITY (mm/min)	< 100	DIN 75200
BURNING BEHAVIOUR	M2	NF P92-503
BURNING BEHAVIOUR	B1	DIN 4102

L - Along T - Across

NOTE : Unless otherwise stated, the figures presented shall be regarded as typical values for the material, and not as a minimum to be satisfied.

Date	Revision	QUALITY CONTROL	TECHNICAL MANAGER
2010.02.12	5		