



ENDUTEX - REVESTIMENTOS TEXTEIS, SA

VIZELA / PORTUGAL



TECHNICAL DATA SHEET

REFERENCE: BACK EX

DESCRIPTION : PVC DOUBLE COATED HIGH TENACITY POLYESTER FABRIC

COMPOSITION : 71 % PVC
29 % POLYESTER

WIDTH : 160 - 250 - 320 - 500 cm

CHARACTERISTIC	SPECIFICATION	METHOD
THICKNESS (mm)	0.40	
TOTAL MASS (g/m ²)	450 ± 40	EN ISO 2286-2
FABRIC MASS (g/m ²)	130 ± 10	EN ISO 2286-2
BREAKING LOAD (daN/50mm)	L.: 250 T.: 140	EN ISO 1421
BREAKING EXTENSION (%)	L.: 20 T.: 25	EN ISO 1421
TEAR STRENGTH (daN)	L.: 14.0 T.: 12.0	DIN 53363
COATING ADHESION (daN/50mm)	min 5.0	EN ISO 2411
COLOUR FASTNESS TO LIGHT	min 5	EN ISO 105-B02
AVERAGE LIGHT TRANSMISSION	18	SF 600 Plus Spectrophotometer
FLAMMABILITY (mm/min)	< 100	DIN 75200

L - Along
T - Across

NOTE : Unless otherwise stated, the figures presented shall be regarded as typical values for the material, and not as a minimum to be satisfied.

Date	Revision	QUALITY CONTROL	TECHNICAL MANAGER
2007.06.26	2		