



ENDUTEX - REVESTIMENTOS TEXTTEIS, SA

VIZELA / PORTUGAL



TECHNICAL DATA SHEET

REFERENCE: NAUTIPRINT

DESCRIPTION : ONE SIDE PVC COATED HIGH TENACITY POLYESTER WOVEN FABRIC

COMPOSITION : 71 % PVC
29 % POLYESTER

WIDTH : 150 - 220 cm

CHARACTERISTIC	SPECIFICATION	METHOD
THICKNESS (mm)	0.39	
TOTAL MASS (g/m ²)	400 ± 40	EN ISO 2286-2
FABRIC MASS (g/m ²)	115 ± 10	EN ISO 2286-2
BREAKING LOAD (daN/50mm)	L.: 170 T.: 140	EN ISO 1421
BREAKING EXTENSION (%)	L.: 20 T.: 20	EN ISO 1421
TEAR STRENGTH (daN)	L.: 10 T.: 10	EN ISO 4674-1
COATING ADHESION (daN/50mm)	min. 5.0	EN ISO 2411
LOW TEMPERATURE BEND TEST	No cracks at -25°C	EN 1876-1

L - Along
T - Across

NOTE : Unless otherwise stated, the figures presented shall be regarded as typical values for the material, and not as a minimum to be satisfied.

Date	Revision	QUALITY CONTROL	TECHNICAL MANAGER
2008.09.09	0		