



ENDUTEX - REVESTIMENTOS TEXTEIS, SA

VIZELA / PORTUGAL



---

---

TECHNICAL DATA SHEET

---

---

**REFERENCE:** POLYCANVAS FR

**DESCRIPTION :** PVC COATED POLYESTER WOVEN FABRIC

**COMPOSITION :** 44 % PVC  
56 % POLYESTER

**WIDTH :** 160 - 320 - 485 cm

CHARACTERISTIC	SPECIFICATION	METHOD
THICKNESS (mm)	0.30	
TOTAL MASS (g/m <sup>2</sup> )	260 ± 25	EN ISO 2286-2
FABRIC MASS (g/m <sup>2</sup> )	145 ± 10	EN ISO 2286-2
BREAKING LOAD (daN/50mm)	L.: 165 T.: 100	EN ISO 1421
BREAKING EXTENSION (%)	L.: 30 T.: 33	EN ISO 1421
TEAR STRENGTH (daN)	L.: 12.0 T.: 6.0	DIN 53363
FUSION OF PVC COATING	Complete	BS 3424.25A
BURNING BEHAVIOUR	M2	NF P92-503

L - Along T - Across

**NOTE :** Unless otherwise stated, the figures presented shall be regarded as typical values for the material, and not as a minimum to be satisfied.

Date	Revision	QUALITY CONTROL	TECHNICAL MANAGER
2004.04.01	2		