



ENDUTEX - REVESTIMENTOS TEXTEIS, SA

VIZELA / PORTUGAL



---

---

TECHNICAL DATA SHEET

---

---

**REFERENCE:** PRINT FLOOR

**DESCRIPTION :** PVC COATED POLYESTER NONWOVEN

**COMPOSITION :** 95 % PVC  
5 % POLYESTER

**WIDTH :** 140 cm

CHARACTERISTIC	SPECIFICATION	METHOD
THICKNESS (mm)	2.20 ± 0.20	
TOTAL MASS (g/m <sup>2</sup> )	1750 ± 100	EN ISO 2286-2
FABRIC MASS (g/m <sup>2</sup> )	80 ± 8	EN ISO 2286-2
BREAKING LOAD (daN/50mm)	L.: 45 T.: 45	EN ISO 1421
BREAKING EXTENSION (%)	L.: 45 T.: 80	EN ISO 1421
TEAR STRENGTH (daN)	L.: 3.0 T.: 3.0	EN ISO 4674-1
COATING ADHESION (daN/50mm)	min. 5.0	EN ISO 2411
DIMENSIONAL STABILITY (%)	L.: < 2.0% T.: < 2.0 %	6h at 80°C

L - Along  
T - Across

**NOTE :** Unless otherwise stated, the figures presented shall be regarded as typical values for the material, and not as a minimum to be satisfied.

Date	Revision	QUALITY CONTROL	TECHNICAL MANAGER
2008.06.03	0		