



ENDUTEX - REVESTIMENTOS TEXTTEIS, SA

VIZELA / PORTUGAL



---

---

TECHNICAL DATA SHEET

---

---

**REFERENCE:** PRINT RC-3 FR

**DESCRIPTION** : PVC DOUBLE COATED HIGH TENACITY POLYESTER SCRIM

**COMPOSITION** : 62 % PVC  
38 % POLYESTER

**WIDTH** : 137 - 160 - 320 - 500 cm

CHARACTERISTIC	SPECIFICATION	METHOD
THICKNESS (mm)	0.48	
TOTAL MASS (g/m <sup>2</sup> )	340 ± 30	EN ISO 2286-2
FABRIC MASS (g/m <sup>2</sup> )	130 ± 10	EN ISO 2286-2
BREAKING LOAD (daN/50mm)	L.: 200 T.: 120	EN ISO 1421
BREAKING EXTENSION (%)	L.: 18 T.: 18	EN ISO 1421
TEAR STRENGTH (daN)	L.: 20 T.: 12	DIN 53363
COLOUR FASTNESS TO LIGHT	min 6	EN ISO 105-B02
AVERAGE PERMEABILITY OF FABRIC TO AIR (l/m <sup>2</sup> /s)	2700	EN ISO 9237
AVERAGE LIGHT TRANSMISSION	24	SF 600 Plus Spectrophotometer
BURNING BEHAVIOUR	B1	DIN 4102
PERCENTAGE OF OPENING	16	

L – Along T - Across

**NOTE** : Unless otherwise stated, the figures presented shall be regarded as typical values for the material, and not as a minimum to be satisfied.

Date	Revision	QUALITY CONTROL	TECHNICAL MANAGER
2008.09.04	0		