



ENDUTEX - REVESTIMENTOS TEXTEIS, SA

VIZELA / PORTUGAL



TECHNICAL DATA SHEET

REFERENCE: ROOFTEX

DESCRIPTION : PVC DOUBLE COATED POLYESTER WOVEN FABRIC

COMPOSITION : 61 % PVC
39 % POLYESTER

WIDTH : 320 - 485 cm

CHARACTERISTIC	SPECIFICATION	METHOD
THICKNESS (mm)	0.33	
TOTAL MASS (g/m ²)	370 ± 30	EN ISO 2286-2
FABRIC MASS (g/m ²)	145 ± 10	EN ISO 2286-2
BREAKING LOAD (daN/50mm)	L.: 165 T.: 100	EN ISO 1421
BREAKING EXTENSION (%)	L.: 30 T.: 33	EN ISO 1421
TEAR STRENGTH (daN)	L.: 2.8 T.: 3.5	EN ISO 4674-1A
BURNING BEHAVIOUR	M3	NF P92-503

L - Along T - Across

NOTE : Unless otherwise stated, the figures presented shall be regarded as typical values for the material, and not as a minimum to be satisfied.

Date	Revision	QUALITY CONTROL	TECHNICAL MANAGER
2006.11.17	4		